

SEE MORE. DO MORE.

Zebra® product positioning guide – mobile printers

Model	EM 220II™	iMZ™ series	MZ [™] series	RW™ series	QLn™ series	Р4Т™/RР4Т™	
Quick facts							
Max. media width/Max. print width	58mm/48mm	76.2mm/73.7mm	76.2mm/73.7mm	105mm/104mm	112mm/104mm	104.7mm/104mm	
Print Resolution	203dpi	203dpi	203dpi	203dpi	203dpi	203dpi	
Max. print speed	90mm/second	100mm/second	76.2mm/second	76.2mm/second	100mm/second	76.2mm/s (DT)/38.1mm/s (TT)	
Printer languages	ESC/POS	Native CPCL and ZPL™	Native CPCL	Native CPCL with ZPL emulation	Native ZPL,CPCL and ZBI 2.0™	CPCL, ZPL and XML	
Standard connectivity	Serial, USB 1.1	USB 2.0	USB 2.0 & IrDA®	Serial, USB 2.0	Serial, USB 2.0	Serial, USB 2.0	
Optional connectivity	Bluetooth 3.0 (includes support for iOS devices); 802.11b/g (optional)	Bluetooth 2.1 (includes support for iOS devices); 802.11a/b/g/n (optional)	Bluetooth or 802.11b/g	Bluetooth or 802.11b/g	Bluetooth or 802.11a/b/g/n	Bluetooth or 802.11b/g	
Printer							
LCD display	×	×	×	\checkmark	✓	✓	
Standard flash memory (total)	256KB	128MB	8MB	8MB	256MB	8MB	
Standard RAM (total)	128KB	128MB	16MB	16MB	128MB	16MB	
Physical features							
Footprint (D x W x H)	43.6 x 79.5 x 126.7mm	iMZ220™: 57.4 x 80 x 135.6mm iMZ320™: 57.4 x 104.4 x 135.6mm	MZ 220 [™] : 57.4 x 80 x 135.6mm MZ 320 [™] : 57.4 x 104.4 x 135.6mm	RW 220™: 76 x 112 x 173mm RW 420™: 76 x 160 x 175mm	QLn220™: 70 x 89 x 165mm QLn320™: 84 x 117 x 173mm QLn420™: 82.5 x 165 x 187mm	67.2 x 177.8 x 218.4mm	
Weight	0.23kg	iMZ220: 0.32kg iMZ320: 0.34kg	MZ 220: 0.32kg MZ 320: 0.34kg	RW 220: 0.70kg RW 420: 0.98kg	QLn220: 0.57kg QLn320: 0.73kg QLn420: 1.1kg	1.32kg	
IP rating	IP54-rated with soft case	IP42-rated (IP54 with soft case)	IP42-rated; damage-resistant to multiple drops of up to 1.2m to concrete	IP42-rated; damage-resistant to multiple drops of up to 1.9m to concrete	IP43-rated (IP54 with soft case); damage-resistant to multiple drops of up to1.52m to concrete	(IP54 with soft case)	
Media							
RFID	×	×	×	×	×	RP4T ✓ Fully integrated ThingMagic [®] UHF RFID Reader/Encoder	
Media types	Direct-thermal receipt paper or UV coated media	Direct-thermal receipt paper or UV coated media	Direct-thermal receipt paper or UV coated media	Direct-thermal tags or receipt paper, synthetic media, UV coated media, limited label support	Receipts and labels	Direct-thermal or thermal-transfer. Receipts, tags and labels on either synthetic or paper. RFID printing and encoding capabilities	

For further information, or to download an electronic copy of this document, please visit Marketing Store.

Gain more revenue from supplies

Genuine Zebra supplies prolong the life and improve the performance of a Zebra printer. In the table below, we've listed some of the materials available in our ZipShip range. For more information and sizes and formats available from stock, refer to the ZipShip price lists available on **www.accesszebra.com**

			ILn220	QLn320	OL 420 Plus ^{ta}	CLn420	RW 220	RW 420	EM22011	VIZ220	MZ320	MZ	ъчт
Product Name	Description	Key features	0	0	0 4	0	œ	œ	ш	5	5	2	•
Z-Perform™ 1000D 60 Receipt	Uncoated direct-thermal 60-micron receipt paper	Ideal for short-life applications. Not recommended for exposure to sunlight or extreme heat. 5 year archive life after printing.	×	×	×	×	✓	✓	s	1	\$	1	×
Z-Perform 1000D 80 Receipt	Uncoated direct-thermal 80-micron receipt paper	80 micron thickness, offering a more robust alternative to the 60-micron product. Not recommended for exposure to sunlight or extreme heat. 5 year archive life after printing.	1	1	1	1	1	✓	1	J	1	1	1
8000D 10 Year Receipt	Direct thermal, 60 micron, long-term archivable receipt paper	Ideal for applications requiring storage of printed receipts that must remain legible for long periods. 10 year archive life after printing.	1	1	1	1	1	✓	1	J	1	J	×
Z-Perform 1000D	Economy direct thermal paper label with permanent adhesive	Low-cost, acrylic based adhesive. Good image quality, designed for optimal balance of performance and price.	1	1	1	1	×	×	×	×	×	×	1
Z-Select™ 2000D	Premium top-coated direct-thermal paper label with permanent adhesive	Rubber based adhesive, ideal for low temperature use. Optimal image quality, good for high-speed printing requiring premium print quality.	1	1	1	1	×	×	×	×	×	×	1
Z-Select 2000D Removable	Premium direct thermal paper with removable adhesive	Removable adhesive. Optimal image quality, good for high-speed printing requiring premium print quality.	1	1	1	~	×	×	×	×	×	×	1
PolyPro™ 4000D	Top-coated direct-thermal polypropylene label with permanent adhesive	Tear-resistant and water-resistant. Can be used short-term outdoors.	1	1	1	~	×	×	×	×	×	×	1
Z-Perform 1000D 110 Tag	Uncoated direct-thermal 110-micron non-adhesive paper tag	110 micron thickness tag product ideal for shelf-edge tags, coupons, tickets and high-quality receipts. 5 year archive life after printing.	1	1	1	~	1	1	×	×	×	×	1
Z-Ultimate® 3000T White	Premium gloss-white polyester label with permanent adhesive	Thermal transfer. Excellent print quality, good chemical resistance. Superior scratch and smear resistance. UL recognised for indoor and outdoor use when matched with Zebra resin ribbons. Ideal for asset labelling and component tracking.	×	×	×	×	×	×	×	X	×	×	1



Zebra Partner

Integer Solutions Gmbh

www.integer-solutions.com

Z-Perform, Z-Select, ZBI 2.0, ZPL and all product names and numbers are Zebra trademarks, ZipShip is a service mark and Zebra, representation of Zebra Head and Z-Ultimate are registered trademarks of ZIH Corp. All rights reserved. Bluetooth is a registered trademark of Bluetooth SIG, Inc. ThingMagic is a registered trademark of ThingMagic, LLC. UL is a trademark of UL LLC. All other trademarks are the property of their respective owners.

www.zebra.com