

# Xenon Performance (XP) 1932g

## Cordless Area-Imaging Scanner

For high-volume scanning environments such as retail stores, distribution centers, and manufacturing, the Xenon™ Performance (XP) 1932g cordless scanner delivers industry-leading performance and durability.

Incorporating the seventh generation of Honeywell's proven Adaptus™ imaging technology and a one-megapixel imager, the Xenon XP 1932g scanner offers superior scan performance, easily capturing even the most difficult-to-read or damaged codes. Along with a full-shift battery life, this helps to eliminate wasted movements and lost time, improving worker productivity and throughput.

Engineered to 50 drops at 1.8 m (6 ft) and 3,000 tumbles at 0.5 m (1.6 ft), and with an IP42 ingress rating for water and dust, the Xenon XP 1932g scanner delivers class-leading durability. This significantly reduces scanner downtime and service costs, leading to a longer lifecycle and a lower total cost of ownership. The industry's only battery-free, cordless solution, the scanner also offers substantially reduced TCO, removing the time, hassle, expense, and environmental impact associated with batteries.

Designed for fast-moving environments with a high number of transactions, the Xenon XP 1932g scanner protects workers with superior depth of field – reducing the need to bend to reach barcodes on the bottom shelf or bottom of the basket. And with a simple, user-focused design, it offers a stylish appearance that fits into any environment. The Xenon XP 1932g is available in Black or Lyric White models to match the scanner to your environment.

Honeywell's Connected platform drives even greater productivity and throughput for your business. Operational Intelligence software delivers real-time scan data and battery metrics, giving managers



*The Xenon XP 1932g cordless scanner delivers premium performance and class-leading durability for improved employee productivity and maximum uptime – leading to a lower TCO.*

insight into workflows for potential process improvements and user training opportunities. The scanner also provides on-demand visibility into battery health and remaining life, enabling batteries to be replaced before they impact uptime. In the future, workflow analytics delivered by our Connected platform will drive competitive advantage for our customers by providing business insights and benchmarking from every scan.

## FEATURES & BENEFITS



Superior scanning performance, even on damaged and poor-quality barcodes, eliminates wasted seconds from every transaction.



Engineered to withstand 3,000 0.5 m (1.6 ft) tumbles and 50 1.8 m (6 ft) drops, the scanner brings class-leading durability and reliability to any environment.



The scanner is optimized for scanning both digital codes off customer smartphones and merchandise codes by the cashier at the register.



Honeywell's Connected platform delivers on-demand scan and battery insights, enabling higher employee productivity and throughput.



The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates how you deploy and update the scanners in your environment.

# Xenon Performance (XP) 1932g Technical Specifications

## WIRELESS

**Radio/Range:** 2.4 GHz to 2.5 GHz (ISM Band)  
Adaptive Frequency Hopping Bluetooth® v4.2;  
Class 2: 10 m (33 ft) line of sight or BLE: 10 m  
(33 ft) line of sight

### Power Options

#### Battery-Free (SuperCap):

**Number of Scans:** Up to 450 per charge

**Expected Duration of Operation:** ±25 mins  
(5 scans/transaction, 1 min/transaction)

**Expected Charge Time:** 120 seconds,  
30 seconds

**Expected Ready to Go Charge Time (USB,  
Power Adapter):** Typically under 25 seconds,  
15 seconds

**Battery:** 2500 mAh Li-ion minimum

**Number of Scans:** Up to 50,000  
scans per charge

**Expected Duration of Operation:** 14 hours

**Expected Charge Time:** 4.5 hours

**User Indicators:** Good Decode LEDs, Rear View  
LEDs, Beeper (adjustable tone and volume),  
Vibration (adjustable), Charge Status Indicator

## MECHANICAL/ELECTRICAL

### Dimensions (L x W x H)

**Scanner:** 99 mm x 64 mm x 165 mm  
(3.9 in x 2.5 in x 6.5 in)

**Presentation Base:** 160 mm x 90 mm x 91 mm  
(6.3 in x 3.5 in x 3.6 in)

**Desktop/Wall Mount Base:** 226 mm x 67 mm x  
81 mm (8.9 in x 2.6 in x 3.2 in)

### Weight

#### Scanner:

**Battery-Free:** 212 g (7.5 oz)

**With Battery:** 240 g (8.5 oz)

**Presentation Base:** 213 g (7.5 oz)

**Desktop/Wall Mount Base:** 237 g (8.4 oz)

**Operating Power (Charging) Bases:** 2.5W  
(500 mA @5V DC)

**Non-Charging Power (Bases):** 0.75W  
(150 mA @5V DC)

**Host System Interfaces:** USB, Keyboard Wedge,  
RS-232, IBM 46xx (RS485)

## ENVIRONMENTAL

### Operating Temperature

**Scanner:** 0°C to 50°C (32°F to 122°F)

#### Bases:

**Charging:** 5°C to 40°C (41°F to 104°F)

**Non-Charging:** 0°C to 50°C (32°F to 122°F)

**Storage Temperature:** -40°C to 70°C  
(-40°F to 158°F)

**Electrostatic Discharge (ESD) (Scanners  
and Cradles):** ±8 kV indirect coupling plane,  
±15 kV direct air

**Humidity:** 0% to 95% relative humidity,  
non-condensing

**Tumble Spec:** 3,000 0.5 m (1.6 ft)  
tumbles (impacts)

**Drop:** Engineered to withstand 50 1.8 m  
(6 ft) drops to concrete

**Environmental Sealing:** IP42

**Light Levels:** 0 to 100,000 lux  
(9,290 foot-candles)

## SCAN PERFORMANCE

**Scan Pattern:** Area Image (1240 x 800  
pixel array)

**Motion Tolerance:** Up to 460 cm/s (181 in/s)  
for 13 mil UPC at optimal focus

### Scan Angle

#### SR:

**Horizontal:** 41°

**Vertical:** 33°

#### HD:

**Horizontal:** 41°

**Vertical:** 33°

**Print Contrast:** 20% minimum  
reflectance difference

**Roll, Pitch, Skew:** ±360°, ±45°, ±65°

**Decode Capabilities:** Reads standard 1D, PDF,  
2D, Postal Digimarc, and OCR symbologies  
Note: Decode capabilities dependent  
on configuration

**Warranty:** 3-year factory warranty  
(Note: Super-Cap Pack warranty is 5 years;  
Battery Pack warranty is 1 year.)

# Xenon Performance (XP) 1932g Technical Specifications

## DECODE RANGES (DoF)

TYPICAL PERFORMANCE*	STANDARD RANGE (SR)	HIGH DENSITY (HD)
<b>NARROW WIDTH</b>		
3 mil Code 128	58 mm – 143 mm (2.3 in – 5.6 in)	Coming Soon
5 mil Code 39	46 mm – 259 mm (1.8 in – 10.2 in)	
10 mil Code 39	0 mm – 536 mm (0 in – 21.1 in)	
13 mil UPC	19 mm – 642 mm (0.7 in – 25.3 in)	
15 mil Code 128	21 mm – 754 mm (0.8 in – 29.7 in)	
20 mil Code 39	25 mm – 989 mm (1 in – 38.9 in)	
5 mil PDF417	50 mm – 169 mm (2 in – 6.7 in)	
6.7 mil PDF417	27 mm – 234 mm (1.1 in – 9.2 in)	
7.5 mil DM**	46 mm – 184 mm (1.8 in – 7.2 in)	
10 mil DM**	27 mm – 255 mm (1.1 in – 10 in)	
20 mil QR	10 mm – 515 mm (0.4 in – 20.3 in)	

\* Performance may be impacted by barcode quality and environmental conditions.

\*\* Data Matrix (DM)

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance).

For a complete listing of all supported barcode symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies).

Adaptus and Xenon are trademarks or registered trademarks of Honeywell International Inc. in the United States and/or other countries.

The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc.

All other trademarks are the property of their respective owners.

### For more information

[www.honeywellaidc.com](http://www.honeywellaidc.com)

### Honeywell Safety and Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-582-4263

[www.honeywell.com](http://www.honeywell.com)



Integer Solutions GmbH

Industriestraße 4

D-61200 Wölfersheim

Tel. +49 (0)6036-90557-0

[office@integer-solutions.com](mailto:office@integer-solutions.com)