# **THOR VM3A**

# Vehicle-Mounted Computer

Designed for use in the toughest distribution centers, manufacturing facilities and freight operations, the Thor™ VM3A computer is the industry's most capable full-sized vehiclemounted mobile computer, delivering unmatched operational efficiences.

The Thor VM3A vehicle-mounted computer offers breakthrough features designed to eliminate downtime and maximize capital investment. The rugged, Android  $^{\rm M}$ -based Thor VM3A device also offers all the advantages of Honeywell's Mobility Edge  $^{\rm M}$  platform – including the ability to accelerate provisioning, application certification and deployment across the enterprise. The Thor VM3A is upgradable to Android R, and features extended security update support to maximize return on customer investment and provide a lower overall total cost of ownership (TCO). The device's advanced enterprise configuration and software support tools also simplify frequently repeated tasks such as unit setup and distribution of security and software updates.

Compact, ergonomic and powerful, the Thor VM3A vehicle-mounted computer has numerous breakthrough features designed to maximize productivity, minimize visual obstructions and reduce or eliminate downtime. The powerful Qualcomm® 660 processor, integrated keyboard and 2x2 MIMO WLAN communications keep workers connected and productive. Built to withstand extreme temperatures, the device's large 12-inch display, readable both indoors and outdoors, supports both resistive and capacitive touchscreen options, and is available with an optional screen defroster for use in cold storage and freezer environments.

The Smart Dock feature delivers immediate savings on support and maintenance costs while maximizing efficiency, enabling users to quickly shift computers as vehicles fail or workloads change. The field-replaceable front panel allows enterprises to minimize investments in spare parts by substituting low-cost spare front panels for spare computers and saves valuable time and maintenance costs by leveraging in-house staff to service touchscreen or keyboard failures.



The Thor VM3A full-sized, vehicle-mounted computer delivers unmatched operational efficiencies in the toughest distribution center environments

# FEATURES AND BENEFITS



The Smart Dock feature enables mounting and removal in seconds without affecting the cabling, saving on support and maintenance costs while minimizing capital expenses.



The field-replaceable front panel reduces maintenance costs by enabling on-site unskilled personnel to service the most wear- and abuse-prone components rather than returning them to the repair depot.



Security update availability is just as important as computer durability for maximizing a computer's useful life. Mobility Edge products provide five more years of security updates than a typical Android device.



No need to choose between optimizing productivity and minimizing IT support costs: All Honeywell Mobility Edge computers share a common hardware and software platform. From an IT perspective, they are all the same product.



The Mobility Edge hardware platform and enterprise lifecycle tools drive an integrated, repeatable, scalable approach for accelerated and secure development, deployment, performance and lifecycle management.



Honeywell Partner

<u>Beratung-Verkauf-Service</u> Integer Solutions GmbH Industriestraße 4, 61200 Wölfersheim Tel.: +49-6036-90557-0 www.integer-solutions.com



# THOR VM3A Technical Specifications

### SYSTEM ARCHITECTURE

Processor: 2.2 GHz Qualcomm Snapdragon™ 660 octa-core Operating System: Android 9 Pie Memory: 4 GB RAM, 32 GB Flash Storage Expansion: User-accessible microSD card up to 512 GB (SDXC/SDHCcompliant)

Audio: Audio for headset, integrated stereo speakers with adjustable volume control, integrated microphone

# Input/Output:

Enhanced Dock: 2x powered RS-232 COM ports, 1x USB 2.0 powered host port Type A, 3 additional USB 2.0 powered host ports, 1x USB 2.0 Client port, 1x Ethernet RJ45 port, 1x headset port, DC power input and ignition control input

Standard Dock: 2x powered RS-232 COM ports, 1x USB 2.0 powered host port, 1x USB 2.0 Client port, 1x headset port, DC power input and ignition control input

Sensors: Ambient light sensor, accelerometer, gyroscope, magnetometer

# **MECHANICAL**

### **Dimensions:**

**Computer:** 318 mm x 260 mm x 62 mm  $(12.5 \text{ in } \times 10.3 \text{ in } \times 2.4 \text{ in})$ 

**Dock:** 180 mm x 155 mm x 54 mm  $(7.1 \text{ in } \times 6.1 \text{ in } \times 2.1 \text{ in})$ 

Assembled Depth: 104 mm (4.1 in)

**Computer:** 3.0 kg (6.65 lbs) Standard Dock: 1.5 kg (3.2 lbs) Enhanced Dock: 1.1 kg (2.4 lbs) Dock weights include mounting ball Operating Temperature: -30°C to +50°C

(-22°F to +122°F) Storage Temperature: -30°C to +50°C

(-22°F to +122°F)

**Humidity**: 5% to 95% non-condensing Environmental Sealing: Independently certified to meet IP66 standards for moisture and particle resistance

**ESD:** EN 55024:2010 (enhanced ESD to

8 kV direct and 15 kV air)

Vibration: Proprietary Random Profile exceeding MIL-STD-810F, composite

wheeled vehicles

**Shock:** SAE-J1455 (MIL-STD-810g-4.6.6 Procedure V-Crash Hazard Shock Test)

### STRUCTURE

Power Supply & UPS: 10 to 60V DC isolated, optional external converters for AC (90-240V AC) and extended range DC (60-150V DC); integrated Li-lon maintenance UPS with 30-min life at 0°C (32°F)

# Display:

**Indoor:** 307 mm (12.1 in) XGA (1024 x 768) LED backlit display. 400 NIT, optional screen blanking **Outdoor:** 307 mm (12.1 in) XGA (1024 x 768) LED backlit display, 900 NIT, optional screen blanking

Touch Panel: Standard: Industrial touch panel with resistive touch and support for finger touch and standard stylus

Multitouch: Optional industrial touch panel with Projected Capacitance touch for finger and conductive stylus; hardened glass overlay

Cold Storage: Optional industrial resistive touchscreen with integrated defroster Integrated Keypad: Seven programmable

multi-function keys

Audio: Audio for headset, integrated stereo speakers with adjustable volume control, integrated microphone

# WIRELESS CONNECTIVITY

WLAN: IEEE 802.11 a/b/g/n/ac; Wi-Fi Alliance Certified, 2x2 MU-MIMO Additional WLAN Features: 802.11

d/h/i/r/k/w

WLAN Security: OPEN, WEP, WPA/WPA2 (Personal and Enterprise)

Supported EAP: TLS, PEAP, TTLS, PWD, FAST, LEAP CCX Version 4 compliant WLAN Antennas: Dual internal antennas, dual external remote and direct connect antenna accessories; 2x SMA connectors for external WLAN antennas

Bluetooth®: Class 1.5 V5.0 Bluetooth and

Bluetooth Profiles: HFP, PBAP, A2DP,

AVRCP, OPP, SPP, GATT

NFC: Integrated Near Field Communication

## SOFTWARE

Honeywell Power Tools and Demos Terminal Emulator Enterprise Browser Application Launcher and Lockdown **Provisioning Tools** Honeywell Mobility SDKs for Android, Web

Support for Third-Party MDM Solutions

# WARRANTY

and Xamarin

One-year factory warranty

# **SERVICE PLANS**

Optional service programs offer worry-free mobile computing

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies

Thor and Mobility Edge are trademarks or registered trademarks of Honeywell International Inc

Android is a trademark or registered trademark of Google LLC.

Qualcomm and Snapdragon are trademarks or registered trademarks of Qualcomm Incorporated.

Bluetooth is a trademark or registered trademark of Bluetooth SG. Inc.

All other trademarks are the property of their respective owners.

# For more information

www.honeywellaidc.com

Thor VM3A Data Sheet | Rev B | 03/20 © 2020 Honeywell International Inc.



**Honeywell Partner** Beratung-Verkauf-Service Integer Solutions GmbH Industriestraße 4, 61200 Wölfersheim Tel.: +49-6036-90557-0 www.integer-solutions.com



